Specifications

Information


The K18B is a single 18" low frequency enclosure designed for sub-bass reinforcement to K Compact series in a wide variety of fixed installation.




Key Features

- High quality plywood
- Compact vented sub-bass
- Direct radiating 18"(460mm) sub-woofer)
- High temperature 4" (100mm) voice coil
- Top hat fitting for pole mounting to K12/K15

Drawing







본사. 경기도 광주시 오포읍 오포안로 151 http://www.chris-system.com info@chris-system.com Tel. 070 7727 7030 Fax. 031 764 7030 ©S3GLOBAL Corp.

Best always comes from basic. Designed by CHRIS-SYSTEM, Seoul, South Korea




Specifications


K 18B

Technical Specifications	
Туре	Subwoofer System
Impedance	8 Ohm
Power (Program / Peak)	1200 Watts / 2400 Watts
Sensitivity 2.83V / 1m	100 dB 1watt/1 metre
Max SPL	128 dB (cont. max SPL / 1m), 134 dB peak
Frequency response -3dB	35 Hz - 300 Hz
Dispersion	
Product Features	
Components	1 x 18" Low Frequency Driver
Crossover	Passive
Connectors	2 x Speakon Connectors NL4
Dimensions (W x H x D)	561 mm x 542mm x 780 mm
Weight (Kg)	45
Colour	Black
Options	Available in white or Ral colours on request.
Rigging	-
Additional Descriptive Data	18 mm Ply construction, with durable scratch resistant black textured paint finish, kick-proof steel grill finished with aluminium Chris-system logo.

Frequency Response



Impedance Response



본사. 경기도 광주시 오포읍 오포안로 151 http://www.chris-system.com info@chris-system.com Tel. 070 7727 7030 Fax. 031 764 7030 ©S3GLOBAL Corp.

Best always comes from basic. Designed by CHRIS-SYSTEM, Seoul, South Korea

